



Certificate of Test Compliance

Worked Performed For:
Pelican Products
23215 Early Ave.
Tustin, CA 90505

Job No. 10583
Contract No. N/A
Purchase Order No. 4500275880 ; 4500273821
Date 03/30/2023

Dust (IP6X) Test

Test Requirements:

Kelly Space & Technology Inc. certifies that the Case, Part No. 1300 - 10.67" L x 9.76" W x 6.89" H was subjected to Dust IP6X per IEC 60529 (IP6X) Par. 13.4 & 13.6.

Pre-Conditioning:

Temperature: 15°C to 35°C
Humidity: 25% to 75%
Dust: Talcum Powder
Dust Concentration: 2 Kg per cubic meter test chamber volume
Duration: 8 Hours

The testing was completely and correctly performed in accordance with IEC 60529 (IP6X) Par. 13.4 & 13.6. specifications. Complete test results are documented in Kelly Space & Technology, Inc. Test Report No. 10583.

Test Summary:

Place the test specimen in a test chamber. Establish a dust concentration of 2 Kg per cubic meter test chamber volume. Expose the test specimen to this dust environment for 8 hours.

Remove accumulated dust from the specimen by brushing, wiping, shaking, taking care to avoid introducing additional dust to the test item. Do not remove dust by either air blast or vacuum cleaning. Perform visual examination for evidence of damage, penetration, or deterioration.

All testing was performed per the test requirements and test summary stated above. There was no visible evidence of dust penetration or damage was observed to the case.

ISO Certification

Available Upon
Request

Prepared by:

Farrah Morones, Environmental Test
Operations Manager

Approved By:

Mike Gallo, CEO & President



Certificate of Test Compliance

Worked Performed For:
Pelican Products
23215 Early Ave.
Tustin, CA 90505

Job No. 10583
Contract No. N/A
Purchase Order No. 4500275880 ; 4500273821
Date 04/06/2023

Dust (IP6X) Test

Test Requirements:

Kelly Space & Technology Inc. certifies that the Case, Part No. 1595 - 17.79" L x 10.63" W x 28.51" H was subjected to Dust IP6X per IEC 60529 (IP6X) Par. 13.4 & 13.6.

Pre-Conditioning:

Temperature: 15°C to 35°C
Humidity: 25% to 75%
Dust: Talcum Powder
Dust Concentration: 2 Kg per cubic meter test chamber volume
Duration: 8 Hours

The testing was completely and correctly performed in accordance with IEC 60529 (IP6X) Par. 13.4 & 13.6. specifications. Complete test results are documented in Kelly Space & Technology, Inc. Test Report No. 10583.

Test Summary:

Place the test specimen in a test chamber. Establish a dust concentration of 2 Kg per cubic meter test chamber volume. Expose the test specimen to this dust environment for 8 hours.

Remove accumulated dust from the specimen by brushing, wiping, shaking, taking care to avoid introducing additional dust to the test item. Do not remove dust by either air blast or vacuum cleaning. Perform visual examination for evidence of damage, penetration, or deterioration.

All testing was performed per the test requirements and test summary stated above. There was no visible evidence of dust penetration or damage was observed to the case.

ISO Certification

Available Upon
Request

Prepared by:

Farrah Morones, Environmental Test
Operations Manager

Approved By:

Mike Gallo, CEO & President



Certificate of Test Compliance

Worked Performed For:
Pelican Products
23215 Early Ave.
Tustin, CA 90505

Job No. 10583
Contract No. N/A
Purchase Order No. 4500275880 ; 4500273821
Date 03/30/2023

Dust (IP6X) Test

Test Requirements:

Kelly Space & Technology Inc. certifies that the Cases, Part No. 1700 - 38.45" L x 16.38" W x 6.14" H was subjected to Dust IP6X per IEC 60529 (IP6X) Par. 13.4 & 13.6.

Pre-Conditioning:

Temperature: 15°C to 35°C
Humidity: 25% to 75%
Dust: Talcum Powder
Dust Concentration: 2 Kg per cubic meter test chamber volume
Duration: 8 Hours

The testing was completely and correctly performed in accordance with IEC 60529 (IP6X) Par. 13.4 & 13.6. specifications. Complete test results are documented in Kelly Space & Technology, Inc. Test Report No. 10583.

Test Summary:

Place the test specimen in a test chamber. Establish a dust concentration of 2 Kg per cubic meter test chamber volume. Expose the test specimen to this dust environment for 8 hours.

Remove accumulated dust from the specimen by brushing, wiping, shaking, taking care to avoid introducing additional dust to the test item. Do not remove dust by either air blast or vacuum cleaning. Perform visual examination for evidence of damage, penetration, or deterioration.

All testing was performed per the test requirements and test summary stated above. There was no visible evidence of dust penetration or damage was observed to the case.

ISO Certification

Available Upon
Request

Prepared by:

Farrah Morones, Environmental Test
Operations Manager

Approved By:

Mike Gallo, CEO & President



Certificate of Test Compliance

Worked Performed For:
Pelican Products
23215 Early Ave.
Tustin, CA 90505

Job No. 10583
Contract No. N/A
Purchase Order No. 4500275880 ; 4500273821
Date 03/30/2023

Dust (IP6X) Test

Test Requirements:

Kelly Space & Technology Inc. certifies that the Case, Part No. 1720 - 44.48" L x 16.08" W x 6.25" H was subjected to Dust IP6X per IEC 60529 (IP6X) Par. 13.4 & 13.6.

Pre-Conditioning:

Temperature: 15°C to 35°C
Humidity: 25% to 75%
Dust: Talcum Powder
Dust Concentration: 2 Kg per cubic meter test chamber volume
Duration: 8 Hours

The testing was completely and correctly performed in accordance with IEC 60529 (IP6X) Par. 13.4 & 13.6. specifications. Complete test results are documented in Kelly Space & Technology, Inc. Test Report No. 10583.

Test Summary:

Place the test specimen in a test chamber. Establish a dust concentration of 2 Kg per cubic meter test chamber volume. Expose the test specimen to this dust environment for 8 hours.

Remove accumulated dust from the specimen by brushing, wiping, shaking, taking care to avoid introducing additional dust to the test item. Do not remove dust by either air blast or vacuum cleaning. Perform visual examination for evidence of damage, penetration, or deterioration.

All testing was performed per the test requirements and test summary stated above. There was no visible evidence of dust penetration or damage was observed to the case.

ISO Certification

Available Upon
Request

Prepared by:

Farrah Morones, Environmental Test
Operations Manager

Approved By:

Mike Gallo, CEO & President



Certificate of Test Compliance

Worked Performed For:
Pelican Products
23215 Early Ave.
Tustin, CA 90505

Job No. 10583
Contract No. N/A
Purchase Order No. 4500275880 ; 4500273821
Date 03/30/2023

Dust (IP6X) Test

Test Requirements:

Kelly Space & Technology Inc. certifies that the Case, Part No. 1750 - 53.06" L x 10.05" W x 5.13" H was subjected to Dust IP6X per IEC 60529 (IP6X) Par. 13.4 & 13.6.

Pre-Conditioning:

Temperature: 15°C to 35°C
Humidity: 25% to 75%
Dust: Talcum Powder
Dust Concentration: 2 Kg per cubic meter test chamber volume
Duration: 8 Hours

The testing was completely and correctly performed in accordance with IEC 60529 (IP6X) Par. 13.4 & 13.6. specifications. Complete test results are documented in Kelly Space & Technology, Inc. Test Report No. 10583.

Test Summary:

Place the test specimen in a test chamber. Establish a dust concentration of 2 Kg per cubic meter test chamber volume. Expose the test specimen to this dust environment for 8 hours.

Remove accumulated dust from the specimen by brushing, wiping, shaking, taking care to avoid introducing additional dust to the test item. Do not remove dust by either air blast or vacuum cleaning. Perform visual examination for evidence of damage, penetration, or deterioration.

All testing was performed per the test requirements and test summary stated above. There was no visible evidence of dust penetration or damage was observed to the case.

ISO Certification

Available Upon
Request

Prepared by:

Farrah Morones, Environmental Test
Operations Manager

Approved By:

Mike Gallo, CEO & President



Certificate of Test Compliance

Worked Performed For:

Pelican Products
23215 Early Ave.
Tustin, CA 90505

Job No. 10583

Contract No. N/A

Purchase Order No. 4500275880 ; 4500273821

Date 03/30/2023

Dust (IP6X) Test

Test Requirements:

Kelly Space & Technology Inc. certifies that the Cases, Part No. 1755 – 57.81" L x 16.71" W x 8.86" H was subjected to Dust IP6X per IEC 60529 (IP6X) Par. 13.4 & 13.6.

Pre-Conditioning:

Temperature: 15°C to 35°C
Humidity: 25% to 75%
Dust: Talcum Powder
Dust Concentration: 2 Kg per cubic meter test chamber volume
Duration: 8 Hours

The testing was completely and correctly performed in accordance with IEC 60529 (IP6X) Par. 13.4 & 13.6. specifications. Complete test results are documented in Kelly Space & Technology, Inc. Test Report No. 10583.

Test Summary:

Place the test specimen in a test chamber. Establish a dust concentration of 2 Kg per cubic meter test chamber volume. Expose the test specimen to this dust environment for 8 hours.

Remove accumulated dust from the specimen by brushing, wiping, shaking, taking care to avoid introducing additional dust to the test item. Do not remove dust by either air blast or vacuum cleaning. Perform visual examination for evidence of damage, penetration, or deterioration.

All testing was performed per the test requirements and test summary stated above. There was no visible evidence of dust penetration or damage was observed to the case.

ISO Certification
Available Upon
Request

Prepared by:

Farrah Morones, Environmental Test
Operations Manager

Approved By:

Mike Gallo, CEO & President