

- Engineered to provide secure transport for rack mountable electronics
- Available in 3U, 4U, 5U, 7U, and 9U
- Equipment payload weight ranges for 3U 5U = 80-100 lbs. (36-45 kg) per case
- Equipment payload weight ranges for 7U 9U = 100-170 lbs. (45-77 kg) per case
- Black case with Anti-Reflective zinc cobalt black (HCB) catch-and-strike hardware
- 2 Lockable Cable Catches per lid to provide security for your equipment
- Black stainless steel handles
- Molded stacking ribs and coupling catches to secure cases when stacked
- Lid hangers for lid storage while in use
- 19" (48 cm) wide, 33" (83 cm) deep fixed square hole frame for universal equipment fit
- Choice of SAE 10-32 or Metric M6 clip nuts
- Sealed gasket and PRV keeps container watertight and eliminates over pressurization
- 4 removable 3.5" (8.9 cm) heavy duty bottom casters
- REACH and RoHs compliant



DIMENSIONS

Exterior (L×W×D): 45.80 x 27.00 x 12.30"

Rack Depth: 33.00"

Interior Lid Depth: 2.50"

Interior Back Lid Depth: 5.25"

MATERIALS

Body Material: RotoMolded Polyethylene

STANDARD COLORS



WEIGHT

Weight: 51.00 lbs (kg)