

- Engineered to provide secure transport for rack mountable electronics
- Available in 3U, 4U, 5U, 7U, and 9U
- Equipment payload weight ranges for 3U –
  5U = 80-100 lbs. (36-45 kg) per case
- Equipment payload weight ranges for 7U –
  9U = 100-170 lbs. (45-77 kg) per case
- Black case with Anti-Reflective zinc cobalt black (HCB) catch-and-strike hardware
- 2 Lockable Cable Catches per lid to provide security for your equipment
- Black stainless steel handles, and 1 comfort grip plastic handle on the 2" lid for rolling the case
- Molded stacking ribs and coupling catches to secure cases when stacked
- Lid hangers for lid storage while in use
- Choice of SAE 10-32 or Metric M6 clip nuts
- Sealed gasket and PRV keeps container watertight and eliminates over pressurization
- 2 edge casters on 5" lid
- RoHs compliant



## **DIMENSIONS**

Exterior (L×W×D): 45.80 x 27.00 x 20.60"

**Rack Depth:** 33.00"

Interior Lid Depth: 2.50"

Interior Back Lid Depth: 5.25"

## **MATERIALS**

Body Material: RotoMolded Polyethylene

## **STANDARD COLORS**



## **WEIGHT**

Weight: 65.00 lbs ( kg)